

ZENNER Stealth Reader Mobile AMR System

The **Stealth Reader Mobile Automatic Meter Reading System** is designed with the meter reader in mind. Its' compact design and magnet mounted roof antenna wont cramp your passenger compartment and provides an easy platform in moving from vehicle to vehicle. Combined with the **Stealth Reader Meter Interface Unit (MIU)**, **Stealth Reader Handheld Unit**, and **Stealth GPS (Global Positioning System) Receiver**, the **Stealth Reader Mobile AMR System** is a complete data collection platform that will quickly and efficiently gather your meter information on every pass through your system.

In order to help keep you in line with your budget, with ZENNER's **Stealth Reader AMR System** you have the option of using an existing laptop computer, purchasing one locally, or having one provided with the system. All are options in an operating system running your Stealth Reader System. With the **Stealth Reader AMR System**, the operator never has to take their eyes off the road to see if the system is functioning properly. Through the Stealth Reader's audio alert system, the vehicle operator is able to remain focused on the task at hand and drive the routes they are assigned. Audio cues keep the meter reader aware of the system reading progress and alarm status while the system is continuously updating the assigned route. This makes it possible for the operator to keep their eyes on the road and view the visual display only when in the safety of a stationary location.



SPECIFICATIONS

<ul style="list-style-type: none"> • Selectable reading screens • No dedicated vehicle required • Real-time GPS Position tracking • Touchscreen interface • Visual and/or audible feedback: <ul style="list-style-type: none"> ◊ Successful Reads ◊ Unread Meters ◊ Leak Conditions ◊ High Usage ◊ Tamper Conditions ◊ Low MIU Battery ◊ High/Low Audit 	<ul style="list-style-type: none"> • Two-way Communication • Frequency: 902-928 MHz (ISM Band) • Frequency Hopping Spread Spectrum • FCC Licensing: Exempt under Part 15 • Operating Temperature: -40°F to 185°F • USB GPS Receiver • Stealth GPS Receiver Physical Dimensions: <ul style="list-style-type: none"> ◊ Height: 10" ◊ Width: 8" ◊ Depth: 4" ◊ Weight: Less than 3 pounds ◊ Antenna with magnetic mount: 30"
--	---